

PRODUCT  
SPECIFICATION

 **TEREX**®

 **ECOTEC**

# TDS 820

SLOW SPEED SHREDDER



# AGGRESSIVE SLOW SPEED SHREDDER

The TDS 820 is an aggressive slow speed shredder suitable for all types of material. Customisable shredding programs allow operators to configure the machine to their specific requirements, reducing wrappage and maximising production.



# TDS 820

Independent shredding shafts allow for maximum application flexibility.



Key features include the hydrostatic drive offering better protection against contamination and allowing for bi-directional shredding. The double shaft shredder has 2m long shafts with a fully welded tooth configuration, impressive throughput and excellent reduction.

The independent gearboxes enable each shaft to be run separately helping to reduce wrappage and improve the shredding of material.

Additional features include the tipping feeder which increases the feed area. Hopper extensions provide increased capacity in bulky applications.

The TDS 820 is powered by the following engines dependent on geographic area and emission regulations; Scania DC13 330kw (440HP) Tier 4 final for the US and EU, Scania DC13 371kw (497HP) constant speed for the EU.

The machine is manoeuvred via a robust tracked undercarriage making it a great solution for difficult terrain.

# KEY FEATURES



A powerful Scania engine with a low operating speed combined with an efficient hydrostatic drive creates a very responsive shredding action with protection against unshreddable contaminants



User friendly colour display offering simple operation and diagnostics  
 Customisable shredding programs allow operators to tailor the machine for specific applications



Robust German designed shredding chamber  
 Independently driven shafts give excellent shredding performance in even the most challenging of applications



Shaft cutting elements are a fully welded structure with hard-faced edges giving ultimate strength in difficult applications

Excellent service access reduces operator downtime



A separate transfer conveyor with a high specification belt ensures material is effectively removed from below the shredding chamber

## ▼ TECHNICAL DATA



### TRANSPORT DIMENSIONS

Length: 9100mm (29' 10")  
 Width: 2500mm (8' 2")  
 Height: 3200mm (10' 6")  
 Weight: 27,500Kg (60,627lbs)  
 (dependent on options)

### WORKING DIMENSIONS

Length: 11700mm (38' 5")  
 (product belt @ 35°)  
 Width: 2500mm (8' 2")  
 Feed Height: 3200mm (10' 6")  
 Discharge Height:  
 3900mm (12' 10") – 1700mm (5' 7")

### SHREDDING UNIT

Type of shredder: Twin shaft slow speed  
 Shaft Length: 2000mm  
 Shaft diameter: 700mm  
 Torque per shaft: 100 000Nm  
 Tilting feeder capacity: 7m<sup>3</sup>  
 Autolube for shredder shaft bearing

### POWERPACK

Engine:  
 - Scania DC13 331kW (440HP)  
 Tier 4 Final (USA & EU)  
 - Scania DC13 371kW (497HP)  
 Constant Speed (EU)  
 CleanFix variable pitch cooling fan  
 Shredder drive: Twin Hydrostatic  
 (independent shaft drive)  
 Fuel capacity: 500l  
 CAN BUS control system with user friendly colour  
 display offering simple operation and diagnostics

### TRANSFER CONVEYOR

Width: 1300mm (4' 3")  
 Length: 2450mm (8' 0")  
 Max. belt speed: 130m/min (426' 6"/min)

### PRODUCT CONVEYOR

Width: 1400mm (4' 7")  
 Length: 5500mm (18")  
 Max. belt speed: 130m/min (426' 6"/min)

### TRACKED UNDERCARRIAGE (OPTION)

Bolt on tracks  
 500mm (20") shoe  
 2920mm (9' 7") sprocket centres

### OPTIONS

Overband magnet  
 Various shaft/breaker bar configurations  
 Plant Autolube (excluding shredder shafts)  
 800mm hopper extensions

Specification subject to change without notice

## ▼ CUSTOMER SUPPORT

*With you every step of the way*

We work with our customers to understand their equipment needs to select the product most suited to their business requirements. Terex Ecotec customer support incorporates a range of services including parts, technical support, warranty and financial services.



### The Right Part at the Right Time

Terex Ecotec has a full inventory of genuine Terex parts through our global support locations and dealer network. We are committed to getting the right parts delivered at the right time. Using genuine Terex parts ensures optimum performance and reliability.



### Warranty Delivering on our promise so you can keep yours

Terex Ecotec warrants its new equipment to be free of defects in material or manufacture for a specified period from the date the equipment is first used.



### Expert technical support

Terex Ecotec provide highly qualified service personnel to ensure that we have the ability to provide technical support when our customers need it. This support is provided in conjunction with our dealer network. We ensure our customers are supported throughout the lifecycle of their machine.



### Terex Financial Services Financing that works for you

Terex Ecotec are able to offer finance solutions to our customers. Our team of finance professionals know the importance of working closely with customers to understand their unique business challenges as well as their financial goals and requirements. Obtaining financing is often a time-consuming task, so we work hard to provide a reliable, flexible and responsive service.



**Delivering On Our Promises,  
So You Can Keep Yours.**



## DUNGANNON

32 Farlough Road  
Dungannon, Co. Tyrone  
BT71 4DT, Northern Ireland

Tel: +44 (0) 28 87 718 500

## NEWTON

22 Whittier Street  
Newton, New Hampshire  
USA, 03858

Tel: +1 (603) 382 0556

---

Dealer Stamp:

---

February 2019. The material in this document is for information only and is subject to change without notice. TEE assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein. Due to continual product development we reserve the right to change specifications without notice. Any product performance figures given in this brochure are for guidance purposes only. This information does not constitute an expressed or implied warranty or guarantee, but shows text examples provided. These results will vary depending on product settings, screen media and sizes, feed source and types of material being processed. Photographs are for illustrative purposes only. Some or all of the machines in the illustrations may be fitted with optional extra. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries © 2019 Terex Corporation.